

# De Dietrich

## Hood

Ref.: **DHB4934H**



## Product highlights

**HIGH Performance** This hood is classified Energy Label A+. It is the result of a perfectly accomplished design and offers the best in terms of energy savings and efficiency,

**Rotator switch** The rotating handle with a design that matches the oven allows a fine adjustment of the power (10 speeds).

**LED dimmer** This function allows you to adjust the light of your hood on 3 levels in order to adapt it to the atmosphere of your room and to your needs.

### GENERAL

Brand	DE DIETRICH
Commercial code	DHB4934H
EAN code	3660767996663
Customs code	84146000

### FEATURES

Product type	Wall decorative hood
Design type	Box
Width (cm)	90
Finishing	Stainless steel+glass
Colour	
Air vented mode	Recycling or extracting air
Delivered in	Air extraction
Type of engine	Brushless
Total power of the motors (W)	160
Number of motors	1
Motor location	In chimney
Delayed stop	No
LED dimmer	Yes
Fan quantity	1

### PERFORMANCE

Annual energy consumption (kWh)	38,9
Energy efficiency class	A+
Min extraction rate (m3/h)	190
Max extraction rate (m3/h)	540
Extraction rate with boost (m3/h)	735
Min recirculation rate (m3/h)	148
Max recirculation rate (m3/h)	273
Recirculation rate with boost (m3/h)	705
Min noise level (dB) (Extraction)	42
Max noise level (dB) (acoustic pressure)	65
Noise level with Boost (dB) (Extraction)	72
Min noise level (dB) (recirculation)	39
Max noise level (dB) (recirculation)	53
Noise level with Boost (dB) (recirculation)	74
Fluid dynamic efficiency class	A
Light efficiency class	A
Lighting efficiency (Lux)	320
Grease filter efficiency class	E

# De Dietrich

## Hood

Ref.: DHB4934H

CONTROLS & LIGHTS	
Control type	rotator
Number of speed positions (without booster)	9
Booster	Yes
Filters saturation indicator	No
Type of light	Led stripe
Number of lights	2
Total power of the lamps (W)	8

EQUIPMENT	
Type of functions	On/Off;Mood Lighting;Speed
Number of grease filters	3
Grease filter material	Dishwasher safe aluminium
Accessories supplied	Chimney
Reference of charcoal filter	AHFC330
Reference of recycling kit	
Optional accessories	Charcoal filter
Reference of engine	
Reference of the chimney extension	
Air outled diameter (mm)	150 / 120
Deflector	No
Non-return valve	Yes

INSTALLATION	
Fuse (A)	1.2
Voltage (V)	220-240
Frequency (Hz)	50-60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	65X900X505
Min-max chimney height (mm)	630/960
Dimensions of the packed product HxWxD (mm)	540X1000X575
Net weight (kg)	16.5
Gross weight (kg)	20.7

MANUFACTURING	
Availability of spare parts (years)	15
Repair index	