

De Dietrich

Hood

Ref.: DHD7261B



Product highlights

Worktop hood Cooking and suction. The singularity of this hood is to be placed near to the cooking hob, its motor is hidden below the worktop.

Downdraft The suction panel rises with a simple touch of the sensitive control, up to 30 cm above the cooking hob, to play its role with perfection

Lighting LED 1 For the higher respect of the environment and of your well-being, the led lighting presents the advantage to spend 85 % less of electricity and to last 20 times longer than incandescent light bulb.

GENERAL

Brand	DE DIETRICH
Commercial code	DHD7261B
EAN code	3660767964211
Customs code	84146000

FEATURES

Product type	Downdraft
Design type	Downdraft
Width (cm)	120
Finishing	Stainless steel
Colour	Stainless steel
Air vented mode	Recycling or extracting air
Delivered in	Recycling air
Type of engine	
Total power of the motors (W)	275
Number of motors	1
Motor location	In hood
Delayed stop	Yes
LED dimmer	
Fan quantity	1

PERFORMANCE

Annual energy consumption (kW/h)	51,9
Energy efficiency class	
Min extraction rate (m3/h)	280
Max extraction rate (m3/h)	612
Extraction rate with boost (m3/h)	791
Min recirculation rate (m3/h)	250
Max recirculation rate (m3/h)	603
Recirculation rate with boost (m3/h)	633
Min noise level (dB) (Extraction)	39
Max noise level (dB) (acoustic pressure)	58
Noise level with Boost (dB) (Extraction)	65
Min noise level (dB) (recirculation)	41
Max noise level (dB) (recirculation)	68
Noise level with Boost (dB) (recirculation)	74
Fluid dynamic efficiency class	
Light efficiency class	A
Lighting efficiency (Lux)	
Grease filter efficiency class	

CONTROLS & LIGHTS

Control type	Electronic soft touch controls
Number of speed positions (without booster)	4
Booster	
Filters saturation indicator	Yes
Type of light	LED
Number of lights	1
Total power of the lamps (W)	9

De Dietrich

Hood

Ref.: DHD7261B

EQUIPMENT	
Type of functions	Delayed stop;Light;On/Off;Speed
Number of grease filters	2
Grease filter material	Washable aluminium
Accessories supplied	Charcoal filter
Reference of charcoal filter	AK912AE1
Reference of recycling kit	
Optional accessories	
Reference of engine	
Reference of the chimney extension	
Air outled diameter (mm)	150
Deflector	No
Non-return valve	Yes

INSTALLATION	
Fuse (A)	10
Voltage (V)	220-240
Frequency (Hz)	50/60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	742X1180X340
Min-max chimney height (mm)	/
Dimensions of the packed product HxWxD (mm)	415X1310X875
Net weight (kg)	45
Gross weight (kg)	56.0

MANUFACTURING	
Availability of spare parts (years)	15
Repair index	