

# De Dietrich

## Hood

Ref.: DHD7561B



## Product highlights

**Worktop hood 2** This hood can be installed discretely between two dominos or laterally to a cooktop. Cooking fumes and capors are literally sucked up towards the open lid, with incomparable efficiency.

**Flap** Unique, this ultra discreet hood benefits of a motorized opening of the lid by a simple press on the On/Off sensitive touch.

**Worktop hood** Cooking and suction. The singularity of this hood is to be placed near to the cooking hob, its motor is hidden below the worktop.

### GENERAL

Brand	DE DIETRICH
Commercial code	DHD7561B
EAN code	3660767964228
Customs code	84146000

### FEATURES

Product type	Downdraft
Design type	Integrated
Width (cm)	52
Finishing	Stainless steel
Colour	Stainless steel
Air vented mode	Recycling or extracting air
Delivered in	Recycling air
Type of engine	
Total power of the motors (W)	250
Number of motors	1
Motor location	In hood
Delayed stop	Yes
LED dimmer	
Fan quantity	1

### PERFORMANCE

Annual energy consumption (kWh)	87,2
Energy efficiency class	C
Min extraction rate (m3/h)	407
Max extraction rate (m3/h)	645
Extraction rate with boost (m3/h)	
Min recirculation rate (m3/h)	312
Max recirculation rate (m3/h)	589
Recirculation rate with boost (m3/h)	
Min noise level (dB) (Extraction)	58
Max noise level (dB) (acoustic pressure)	67
Noise level with Boost (dB) (Extraction)	
Min noise level (dB) (recirculation)	65
Max noise level (dB) (recirculation)	74
Noise level with Boost (dB) (recirculation)	
Fluid dynamic efficiency class	C
Light efficiency class	
Lighting efficiency (Lux)	0
Grease filter efficiency class	C

### CONTROLS & LIGHTS

Control type	Electronic soft touch controls
Number of speed positions (without booster)	4
Booster	
Filters saturation indicator	Yes
Type of light	
Number of lights	0
Total power of the lamps (W)	21

# De Dietrich

## Hood

Ref.: DHD7561B

EQUIPMENT	
Type of functions	Speed;On/Off;Delayed stop
Number of grease filters	1
Grease filter material	Washable stainless steel
Accessories supplied	Charcoal filter
Reference of charcoal filter	
Reference of recycling kit	
Optional accessories	
Reference of engine	
Reference of the chimney extension	
Air outlet diameter (mm)	
Deflector	No
Non-return valve	Yes

INSTALLATION	
Fuse (A)	10
Voltage (V)	220-240
Frequency (Hz)	50/60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	430X520X140
Min-max chimney height (mm)	/
Dimensions of the packed product HxWxD (mm)	510X610X460
Net weight (kg)	18
Gross weight (kg)	26.0

MANUFACTURING	
Availability of spare parts (years)	15
Repair index	