De Dietrich

Hood Ref.: DHG4653B

Product highlights

Motion control With simple hand gestures, control the suction power of your hood without touching it to avoid fingerprints.

Remote Control It allows you to regulate lighting, functionning and extraction power from distance.

LED dimmer This function allows you to adjust the light of your hood on 3 levels in order to adapt it to the atmosphere of your room and to your needs.

GENERAL	
Brand	DE DIETRICH
Commercial code	DHG4653B
EAN code	3660767996649
Customs code	84146000

FEATURES	
Product type	Filtering unit
Design type	Filtering unit
Width (cm)	55
Finishing	Body in painted metal
Colour	Black
Air vented mode	Recycling or extracting air
Delivered in	Recycling air
Total power of the motors (W)	160
Number of motors	1
Motor location	In hood
Fan quantity	1

PERFORMANCE	
Annual energy consumption (kW/h)	38,1
Energy efficiency class	Α
Min extraction rate (m3/h)	165
Max extraction rate (m3/h)	470
Extraction rate with boost (m3/h)	630
Min recirculation rate (m3/h)	70
Max recirculation rate (m3/h)	220
Recirculation rate with boost (m3/h)	375
Min noise level (dB) (Exctraction)	43
Max noise level (dB) (acoustic pressure)	62
Noise level with Boost (dB) (Exctraction)	69
Min noise level (dB) (recirculation)	40
Max noise level (dB) (recirculation)	65
Noise level with Boost (dB) (recirculation)	74
Fluid dynamic efficiency class	A
Light efficiency class	В
Lighting efficiency (Lux)	192
Grease filter efficiency class	D

CONTROLS & LIGHTS	
Control type	Electronic controls
Number of speed positions	3
Filters saturation indicator	
Type of light	Led stripe
Number of lights	1
Total power of the lamps (W)	6

	EQUIPMENT	
	Type of functions	Speed
	Number of grease filters	1
	Grease filter material	<fr found="" not="" value=""></fr>
	Accessories supplied	
	Reference of charcoal filter	FWK385
	Reference of recycling kit	
	Optional accessories	
	Reference of engine	
	Reference of the chimney extension	
7	Air outled diameter (mm)	150
	Deflector	No
	Non-return valve	Yes

INSTALLATION	
Fuse (A)	1.15
Voltage (V)	220-240
Frequency (Hz)	50-60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	XX
Min-max chimney height (mm)	/
Dimensions of the packed product HxWxD (mm)	XX
Net weight (kg)	8.2
Gross weight (kg)	10.3

MANUFACTURING	
Availability of spare parts (years)	14
Repair index	

De Dietrich

Hood Ref.: DHG4653B

